

ISO 87/50



Spiral-span pins, rule execution

Made in Taiwan
Global standard

0.8

Hot selling


Nominal

35

| Wan | P | | d1 |
|----------|--------------|---|----|
| dard | | | |
| | a l | | |
| Unit: mm | r ' <u> </u> | ι | |

2.5

| d1 m | nin. | 0.85 | 1.05 | 1.25 | 1.62 | 2.13 | 2.65 | 3.15 | 3.67 | 4.2 | 5.25 |
|----------------|---------------|------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| d1 m | ax. | 0.91 | 1.15 | 1.35 | 1.73 | 2.25 | 2.78 | 3.3 | 3.84 | 4.4 | 5.5 |
| d2 m | ax. | 0.75 | 0.95 | 1.15 | 1.4 | 1.9 | 2.4 | 2.9 | 3.4 | 3.9 | 4.85 |
| a appi | OX | 0.3 | 0.3 | 0.4 | 0.5 | 0.7 | 0.7 | 0.9 | 1 | 1.1 | 1.3 |
| S | | 0.07 | 0.08 | 0.1 | 0.13 | 0.17 | 0.21 | 0.25 | 0.29 | 0.33 | 0.42 |
| Min. double sh | near strength | 0.4 | 0.6 | 0.9 | 0.45 | 2.5 | 3.9 | 5.5 | 7.5 | 9.6 | 15 |
| (kN | J) | 0.3 | 0.45 | 0.65 | 1.05 | 1.9 | 2.9 | 4.2 | 5.7 | 7.6 | 11.5 |
| Length | Tolerance | | | | | | | | | | |
| 4 | | | | | | | | | | | |
| 5 | | | | | | | | | | | |
| 6 | +/-0.25 | | \bigcirc | \bigcirc | \bigcirc | \bigcirc | \bigcirc | \bigcirc | | | |
| 8 | | | | \bigcirc | \bigcirc | \bigcirc | \bigcirc | \bigcirc | \bigcirc | 0 | |
| 10 | | | \bigcirc |
| 12 | | | | \bigcirc | | | | \bigcirc | \bigcirc | \bigcirc | |
| 14 | | | | \bigcirc |
| 16 | | | | | | | | \bigcirc | \bigcirc | \bigcirc | |
| 18 | | | | | | \bigcirc | \bigcirc | \bigcirc | \bigcirc | \bigcirc | \bigcirc |
| 20 | +/-0.5 | | | | | | | | \bigcirc | 0 | |
| 22 | | | | | | | (| (| (| 0 | (|
| 24 | 17-0.5 | | | | | | | 0 | \bigcirc | 0 | \bigcirc |
| 26 | | | | | | | (| 0 | O | 0 | \bigcirc |
| 28 | | | | | | 0 | | 0 | | 0 | \bigcirc |
| 30 | | | | | | | | 0 | (| 0 | O |
| 32 | | | | | | | | \bigcirc | | \bigcirc | \bigcirc |





Unit: mm

| Nom | inal | 0.8 | 1 | 1.2 | 1.5 | 2 | 2.5 | 3 | 3.5 | 4 | 5 |
|--------|-----------|-----|---|-----|-----|---|-----|------------|-----|------------|------------|
| Length | Tolerance | | | | | | | | | | |
| 40 | | | | | | | | 0 | | 0 | 0 |
| 45 | +/-0.5 | | | | | | | \bigcirc | | \bigcirc | \bigcirc |
| 50 | | | | | | | | | | | |

I nina@witecsp.com

I TEL: +886229831315