



# Wuxi LKN fastening systems Co.Ltd



D =outer diameter of the insert before installation

W = number of coils

## Tailless Helical wire thread insert metric

Free-running and Screw-lock both are available.

material: SUS304

inner size	pitch	nominal lenth		W number of coil	D		drill diameter
		xd	mm		min	max	
2	0.4	1d	2	3.2	2.45	2.6	2.1
		1.5d	3	5.3			
		2d	4	7.4			
		2.5d	5	9.5			
2.5	0.45	1d	2.5	3.6	3.15	3.35	2.6
		1.5d	3.75	5.9			
		2d	5	8.2			
		2.5d	6.25	10.5			
3	0.5	1d	3	4.2	3.73	3.99	3.1
		1.5d	4.5	6.8			
		2d	6	9.4			
		2.5d	7.5	12			
4	0.7	1d	4	4	4.96	5.28	4.2
		1.5d	6	6.6			
		2d	8	9.1			
		2.5d	10	11.7			
5	0.8	1d	5	4.4	6.15	6.5	5.2
		1.5d	7.5	7.1			
		2d	10	9.9			
		2.5d	12.5	12.6			
		3d	15	15.3			
6	1	1d	6	4.3	7.3	7.6	6.3
		1.5d	9	6.9			
		2d	12	9.6			
		2.5d	15	12.2			
		3d	18	14.9			

order description: eg, Tangless wire insert, M3\*0.5\*1.5D