

SUPPLIER PART #	DESCRIPTION	MODEL / TYPE / REFERENCE	TEMP RANGE	MATERIAL / SPECIFICATION	QUANTITY	UNIT PRICE (EXW)	CURRENCY	SUPPLIER PRICE UP LOC.
1	12.7mm (1/2") -13 UNC Hex Nut			18-8 Stainless Steel	54			
2	12.7mm (1/2") Flat Washer			18-8 Stainless Steel	54			
3	12.7mm (1/2") Spring Lock Washer			18-8 Stainless Steel	54			
4	12.7mm (1/2") Clevis Pin with 19.05mm (3/4") usable length, 25.4mm (1") Overall length & Hairpin Cotter Pin included	McMaster-CARR #62390417		18-8 Stainless Steel	6			
5	12.7mm (1/2") -13 UNC x 38.1mm (1 1/2") Long Hex Head Cap Screw			18-8 Stainless Steel	9			
6	15.875mm (5/8") -11 UNC U-Bolt 187.325mm (7 3/8") Center to Center (For 152.4mm (6") Pipe incl. 2 x Hex Nuts	McMaster-CARR #8987145		304 Stainless Steel	2			
7	6.35mm (1/4") NPT Hex Plug			A-182 304 Stainless Steel	1			
8	25.4mm x 304.8mm (1" x 12") Turnbuckle Ratchet	Patterson Type J		C.S	1			
9	152.4mm (6") 150# RF Blind Flange			A-182 304 Stainless Steel	1			
10	76.2mm (3") x 82.55mm (3 1/4") Pipe Nipple NPT threads on both ends			A-312 304 Stainless Steel	4			
11	50.8mm (2") to 104.775mm (4 1/8") Clamp Range Worm Drive Hose Clamp	McMaster-CARR #563K12		304 Stainless Steel	16			
12	76.2mm (3") FNPT Full Port Ball Valve, PTFE Seats, with lever handle	McMaster-CARR #4649K26		316 Stainless Steel Body	4			
13	76.2mm (3") Easy Fit Barbed Hose Adapter, 76.2mm (3") MNPT one end & 76.2mm (3") Male Hose Barb connection on the other end. 50 PSI Rated	McMaster-CARR #5363K76		316 Stainless Steel	8			
14	76.2mm (3") Cam & Groove Hose with Male Coupling, 76.2mm (3") FNPT One End & 76.2mm (3") Male Cam & Groove Plug Connection on the other end. 200 PSI Rated	McMaster-CARR #53019K57		316 Stainless Steel Body	4			
15	76.2mm (3") Cam & Groove Hose Female Coupling, 76.2mm (3") FNPT One End & 76.2mm (3") Female Cam & Groove Connection on the other end. 200 PSI Rated	McMaster-CARR #53019K137		316 Stainless Steel Body with BUNA-N Seals	4			
16	4.762mm (3/16") Thick Gasket. Closed Cell Sponge with adhesive backing			Neoprene	3			
17	4.762mm (3/16") Thick, Closed Cell Sponge			Neoprene	6			
18	3.175mm (1/8") Thick EPDM Gasket (For 152.4mm (6") 150# RF/ISO ANSI Flange)				1			
19	19.05mm (3/4") -10 UNC x 82.55mm (3 1/4") LG Heavy Hex Bolt with Heavy Hex Nut			A-103, B8	8			
20	Multipurpose Dry-Running Flanged PTFE Sleeve Bearing for 50.8mm (2") Shaft				1			
21	15.875mm (5/8") Graphite-filled Aramid Fibre (Kevlar) Packing	McMaster-CARR #9518K88			1			
22	76.2mm (3") NPT x 25.4mm (1") NPT 3000# Hex Bushing (Bore out center to 52.3875mm (2 1/8") Diameter			A-182 304 Stainless Steel	1			
23	76.2mm (3") Parker E-Z Form GS General Service Hose, 223.52mm (8.8") Minimum bend radius, 635mm (25") - 0mm (0") Pack Lengths, 75 PSI Rated	Parker #7395-3000025			2			
24	15.875mm (5/8") - 11 UNC x 127mm (5") LG Hex Bolt			18-8 Stainless Steel	2			
25	15.875mm (5/8") FW Spring Lock Washer			18-8 Stainless Steel	4			
26	15.875mm (5/8") - 11 UNC FW Hex Nut			18-8 Stainless Steel	4			
27	22.25mm (7/8") -9 UNC x 152.4mm (6") LG Hex Bolt			18-8 Stainless Steel	4			
28	22.25mm (7/8") Spring Lock Washer			18-8 Stainless Steel	8			
29	22.25mm (7/8") -9 UNC Hex Nut			18-8 Stainless Steel	8			
30	12.7mm (1/2") -13 UNC x 44.45mm (1 3/4") LG Head Cap Screw			18-8 Stainless Steel	40			
31	12.7mm (1/2") Flat Washer			18-8 Stainless Steel	80			
32	12.7mm (1/2") Spring Lock Washer			18-8 Stainless Steel	40			
33	12.7mm (1/2") -13 UNC Hex Nut			18-8 Stainless Steel	40			
34	6.35mm (1/4") NPT 3000# Hex Plug			A182 304 Stainless Steel	2			
35	3.175mm (1/8") Pop Rivet			Stainless Steel	MOQ			

Considerations:

- 1) Product / Service Specification
- 2) Pricing structure (incl. Volume discounts if applicable)
- 3) Lead time and delivery schedules
- 4) Minimum order quantities (MOQs)
- 5) Payment terms and conditions
- 6) Warranty or after sales support
- 7) Certifications or compliance standards
- 8) Any additional documentation (e.g. brochures, technical sheets)