

No.	KPO SAP MM Description	Unit of Measure	QTY
1	BOLT,HEXAGONAL: M16 X 40,UNI 5739,ASTM A320 L7M/A194 7M	ШТ	15
2	NIPPLE,PIPE: 1/4 IN MNPT X 1/4IN MNPT,3MM WT,120MM LONG,GRAY,CARBON STEEL,ASTM A350 GR LF2,MANUFACTURED TO ANSI/ASME B16.5,PAINT COATED,NACE MR-01-75	ШТ	8
3	PACKING: GRAPHITE FLEXIBLE,5/16"SQUARE,SUPPLIED AS A ROLL OF 18 FT LENGHT,1 LB SIZE,	ШТ	2
4	KIT,FLANGE INSULATION: 10IN,CL150,RF	КОМПЛЕКТ	6
5	KIT,FLANGE INSULATION: 6IN,CL150,RF,	КОМПЛЕКТ	8
6	150-SP-8.000, KIT,FLANGE INSULATION: 8IN,CL150,RF *	КОМПЛЕКТ	6
7	300-SP-1.000, KIT,FLANGE INSULATION: 1IN,CL300,RF,	КОМПЛЕКТ	6
8	KIT,FLANGE INSULATION: 3IN,CL300,RF,	КОМПЛЕКТ	6
9	300-SP-6.000, KIT,FLANGE INSULATION: 6IN,CL300,RF	КОМПЛЕКТ	6
10	300-SP-8.000, KIT,FLANGE INSULATION: 8IN,CL300,RF	КОМПЛЕКТ	6

11	NUT,LOCK: 25MM,BRASS	ШТ	70
12	BLADE,HACKSAW: - ECLIPSE FLEXIBLE HSS, HACKSAW BLADE, 18TPI, - BLADE LENGTH: 300 MM (12"), - WIDTH: 12.5MM (1/2"), - BLADE THICKNESS: 0.63MM, - MATERIAL: HSS, - NUMBER OF TEETH PER INCH: 18, - PINHOLE DIAMETER: 4MM	ШТ	40
13	SEAT: O-RING,FOR FIREWATER & STORAGE TANKS P/N 120109	ШТ	4
14	COVER: O-RING,FOR FIREWATER & STORAGE TANKS P/N 120110	ШТ	2
15	DIAPHRAGM,:214MM OD X 10MM ID,PTFE.	ШТ	4
16	TAPE,ELECTRICAL: 3M SELF BONDING,23,RUBBER,19MM WIDE,THICKNESS 0.76 MM,SUPPLIED IN ROLL OF 9.15M	ШТ	214
17	TAPE,ELECTRICAL: COLOR: WHITE, PVC, 19MM X 33M, 0.13MM THICK	ШТ	100
18	BLADE,BANDSAW: 11" X 1",14 TPI,BI-METAL GR M42	ШТ	21
19	SEAL,CLOSURE: NITRILE P/N 790003834,OLD P/N 734147202/6, FOR USE ON:14" FUEL GAS FILTER MODEL 204504/FL9	ШТ	2
20	LADDER,EXTENSION: P/N 8269T14	ШТ	2
21	WASHER,TAB: M10,316L STAINLESS STEEL	ШТ	120
22	GASKET,STRAINER: SOFT IRON,FOR 4" 600LB RTJ Y-STRAINER P/N V00892SOFT	ШТ	2

23	INDICATOR,LIVE-LINE FOR 10KV (10 KV, УВН-10С3) УВНУ-10С3-ИП	ШТ	5
24	KEY: TYPE MK AL-CH SYU7/-242,SUITABLE FOR PADLOCK MODEL J-SK3901-70, ORIGINALLY PURCHASED AGAINST AP/X/04/0686	ШТ	50
25	OIL,SILICON: 47V50,FOR PRESSURE GAUGES WIKA, SUPPLIED IN DRUM OF 25 KG	кг	500
26	SEAL,LOCKING: FOR EXTINGUISHER,FIRE	ШТ	5500
27	BUSHING: SIZE D25/36 X 50,BRONZE P/N BUSBS1326/25	ШТ	1
28	SEAL,DOOR: FLEXIBLE,FOR 16" SPHERE LAUNCHER,FOR BOLSHOI CHAGAN FISCAL METERING P/N 3131-0005-06	ШТ	7
29	SET,BEARING: FOR FAN CENTRIMASTER GXLB-5-035-1-1-3-0 P/N GXLB-99-32-035-0	набор	2
30	THINNER: 90-58,AMERCOAT 12,SUPPLIED IN CAN OF 20L	литр	261
31	CABLE: LINER HEAT DETECTOR,TYPE PHSC 190-EPR, NOMINAL 88 DEG C,GRAY,FOR OUTDOOR USE	м	330

32	<p>REGULATOR,HEATED,PRESSURE: MODEL HPR2,100W,SEAT MATERIAL TEFZEL, Go Heated Regulator, model HPR2 1Z23A3J9111 316L Stainless Steel NACE 3.1B material certificates Heating Range; 24deg C 79 Deg C 100 W heater Peek seat material Cv: 0.06 100 BarG max inlet pressure 70 BarG operating pressure 0 - 500 PSI outlet 240 VAC power supply Tamper proof cap Thermal cut out 1/8" NPTF inlet 1/4" NPTF outlet</p>	ШТ	2
33	<p>KIT,SPARES: FOR PRESSURE SAFETY VALVE,TYPE 7000-SMF,CW ORIFICE D(0.785 CM2),75 BAR,INCLUDING: NOZZLE in ASTM A479 316 + Stellite 1 pc Code UF00EQ Disk in ASTM A479 316 + Stellite 1 pc Code UF01A0,SPRING WASHER ASTM A479 316 2 pcs Code UF0805,SPRING in ASTM A313 316 1 pc Code VFM23F,BODY GASKETS in Graphoil +316 2 pcs Code VZ05KY,CAP GASKET in Graphoil +316 1 pc Code VZ05KL,NOZZLE GASKET in Graphoil + 316 1 pc Code VZ05KQ,BALL in ASTEM A276 316 1 pc Code VF04U4,For reference see manual "SAFETY-RELIEF VALVES SU-SMF-SMFN-7000,DRW SERIES 7000-SMF</p>	КОМПЛЕКТ	4
34	<p>FILTER,PRESSURE REGULATOR: FOR HP BOILER STEAM SYSTEM, In P. max 16 bar Out P. 0.5-1 bar T.max 50 C F.max 25 ms manufacture CAMOZZI (Italy)</p>	ШТ	2
35	<p>ANTIFREEZE:CATERPILLAR SUPPLIED IN DRUM OF 209L</p>	ШТ	4
36	<p>MANIFOLD,VALVE: 5WAY,MODEL VMC541,316/SS,6000PSI,MC,232077,INLET/OUTLET 1/2IN NPT F,DRAIN PORT 1/4IN NPT F</p>	ШТ	10
37	<p>TUBE,INNER: CODE 2701T511,SIZE 26</p>	ШТ	60
38	<p>CARTRIDGE: FOR FILTER FA/1-AP-BT, For KOTS</p>	ШТ	2

39	DETECTOR,RUBBER PROFILE,LENGTH CELBAU 53859 390 CM,1) SAFETY EDGE CONTROL UNIT 8K2 230V 2X .TYPE 252.00Z,2) SPIRAL CABLE 900MM STRAIGHT CABLE LENGTH 2000/350.ITEM NO 40015735,3) RUBBER PROFILE NO 6 WITH RESISTOR AND 2 TERMINAL BOXES (LENGTH OF RUBBER PROFILE 3900MM).	ШТ	10
40	ELECTRODE: LYNCOLN KRYO 1N,SPECIFICATION/CLASSIFICATION AWS A5.5-96,E8016-G H4R 2.5 X 350 MM,VACUUM PACKAGING (SEALED SAHARA READY PACK)	КГ	152.1
41	ELECTRODE: LYNCOLN KRYO 1N,SPECIFICATION/CLASSIFICATION AWS A5.5-96,E8016-G H4R 3.2 X 450 MM,VACUUM PACKAGING (SEALED SAHARA READY PACK)	КГ	124.8
42	Sealant, Soudal, Contractors 200MP, white	ШТ	50
43	THERMOCOUPLE: FOR BOILER	ШТ	11
44	GREASE: DIAMANT SILICONFETT,TYPE 2,-40 DEG C/+200DEG C,SUPPLIED IN 1000GR	ШТ	25
45	DISC: GRINDING,METAL BDX DPC 125X6.5X22.2	ШТ	35
46	BRUSH,CUP: 4 RBK DX5.1/2 FACE X 5/8 WHIT BR P/N 253046	ШТ	40
47	SLING,LIFTING: DUPLEX,1 M,PURPLE P/N 7293010	ШТ	31
48	SLING,WEBBING: 1 TONNE LOAD,2 M	ШТ	25
49	SLING,LIFTING: DUPLEX,3 M,PURPLE P/N 7293029	ШТ	18

50	SLING,WEBBING: 1 TONNE LOAD,4m,RS 729-3066 Replacement of 234-2154	ШТ	25
51	SLING,WEBBING: 2 TONNE LOAD,3 M	ШТ	27
52	SLING,WEBBING: 2 TONNE LOAD,6 M	ШТ	20
53	SLING,LIFTING: DUPLEX,1 M,YELLOW	ШТ	15
54	SLING,WEBBING: 3 TONNE LOAD,3 M	ШТ	18
55	SLING,LIFTING: DUPLEX,5 M,YELLOW	ШТ	33
56	SLING,LIFTING: DUPLEX,6 M,YELLOW	ШТ	27
57	SLING,LIFTING: DUPLEX,3 M,BROWN	ШТ	24
58	LIQUID,DIAMOND: KEMET,TYPE K,STD 6,MICRON 400GR, TYPE K STD 6 MICRON 400 GR	ШТ	5
59	FLUID,LUBRICATING: KEMET,TYPE K,2.5LTR, TYPE K FLUID LUBRICATING 2.5LTR	ШТ	2
60	O-RING: 2-112,BUNA-N,FOR PRESSURE CONTROL VALVE WITH MODEL LG3-4E	ШТ	1
61	O-RING: 2-012,BUNA-N,FOR PRESSURE CONTROL VALVE WITH MODEL LG3-4E	ШТ	1
62	O-RING: 2.011,BUNA-N,FOR 60-7300-PCV-012	ШТ	1

63	DIAPHRAGM: FOR ACTUATOR #3,FOR PRESSURE CONTROL VALVE WITH MODEL LG3-4E	ШТ	1
64	NOZZLE: 1500,LP-D,1/2IN,MALE,FOR HYDROSEAL VALVE,RELIEF 1/2IN,NPT,MODEL 15D1M0C30,FOR AIR RECEIVER,10.7 BAR SET PRESSURE	ШТ	8
65	GRAPHIT: TYPE MOLYCOTE 1000 FOR BOLTS,TO BE SUPPLIED 1000G	ШТ	95
66	FLUID: LUBRICATING,450 MLTR,TYPE OS	ШТ	2
67	PLATE: 6000X2000X12MM, MATERIAL 09G2S AS PER GOST 27772-88, Dimensions as per GOST 19903-74	ШТ	1
68	BOLT,EYE: M22,METRIC THREAD,COLLARED P/N 2652-20283	ШТ	6
69	NIPPLE,HEX 3/4" X 1/2" MALE,P/N 51205K202	ШТ	4
70	ТЕRМОСТАТ: АS WATER.20 TO 80 DEGREE C.FOR DIESEL ENGINE.	ШТ	1
71	FILTER, OIL: FOR GENERATOR MOSA 12054 HBS	ШТ	4
72	TUBE: INSTRUMENT, INCONEL, DIA 12MM X 1.5MM WT	ШТ	30
73	DISSOLVENT 647,FOR GAS TURBINE GENERATION Bottle of 0.5 L	ШТ	10

74	MULTIMETALL,STALL KPL,SUPPLIED IN CAN OF 1,5 KG.UGK PERMISSION FOR PRODU CT USING SHOULD BE PROVIDED BY SUPPLIER,SET CONSIST OF: COMPONENT A 0GR.,COMPONENT B - 550GR	ШТ	6
75	BELZONA 1111 (SUPER METAL) A TWO-PART REPAIR COMPOSITE FOR METAL REPAIR AND RESURFACING BASED ON SOLVENT FREE EPOXY RESIN REINFORCED WITH SILICON STEEL ALLOY, supplied 8 x 1 Kg	комплект	3
76	ALLEN SCREW: M8X65 ISO4762; 8.8-A2B; REF DWG No 1114930000/1G/01	ШТ	10
77	ALLEN SCREW: M5X35 ISO4762 SCHAFT A; 8.8-A2B; REF DWG NO 1114930000/1G/01	ШТ	5
78	Valve,type: VT, 3-Way, 1/2", manufacturer ERIE	ШТ	2
79	KIT, KIT FOR BREATHER SAFETY VALVE WITH S/N 151500-333 AND TAG# 70-2200-PSV-031, OEM: FNC. CONSIST OF: 1) PALLET PRESSURE AND VACUUM SIDE-2 EA,MPN: SVA52000001251B 2) SEATS-2 EA, MPN:SVA52000001252B 3) GASKET SEATS-2 EA, MPN:SVA87000001253C 4) GASKET COVER-2 EA, MPN:SVA87000001255C.	комплект	1
80	THERMOSTAT, ELECTRONIC TYPE, SURFACE SENSING, MAX LOAD 32 A HEAT TRACING TYPE ETS-05-H2-EP	ШТ	81
81	GREASE, SILICONE MOLYKOTE 33 LIGHT, 100G, MANUFACTURE DOW CORNING	ШТ	5
82	GREASE, SILICONE MOLYKOTE 33 MEDIUM, 100G, MANUFACTURE DOW CORNING	ШТ	5

83	GREASE, SILICONE MOLYKOTE 55 ORING, 100G, MANUFACTURE DOW CORNING	шт	5
84	UNIT,ELECTRONIC: POINT LEVEL CONTROL,33 V,150 mA,1 W,EEX IA IIC T4, KEMA NO. EX-93.C.9410X AMBIENT TEMPERATURE: -55 DEG C / +75 DEG C (ANALOGUE OF SAP ITEM 13340 – IS ONLY ELECTRONIC UNIT WITHOUT ENCLOSURE)	шт	1
85	SEAL REPAIR, SET: for PRESSURE REDUCING VALVE II-M190-FPM; POS. 062, 071, 245, 249, 254, 351, 356, 381 AS PER INSTRUCTIONS FOR MAINTENANCE AND REPAIR.	шт	3