

| Sr # | Description   | Qty      |
|------|---|----------|
| 1    | Retaining Ring External, DIN 471-1.4122, $\phi = 4\text{mm}$                                    | 1000     |
| 2    | Retaining Ring External, DIN 471-1.4122, $\phi = 5\text{mm}$                                    | 4000     |
| 3    | Retaining Ring External, DIN 471-1.4122, $\phi = 6\text{mm}$                                    | 2500     |
| 4    | Retaining Ring External, DIN 471-1.4122, $\phi = 8\text{mm}$                                    | 1500     |
| 5    | Retaining Ring External, DIN 471-1.4122, $\phi = 9\text{mm}$                                    | 1500     |
| 6    | Retaining Ring External, DIN 471-1.4122, $\phi = 10\text{mm}$                                   | 2000     |
| 7    | Retaining Ring External, DIN 471-1.4122, $\phi = 19\text{mm}$                                   | 2500     |
| 8    | Retaining Ring External, DIN 471-1.4122, $\phi = 30\text{mm}$                                   | 500      |
| 9    | Retaining Ring External, DIN 471-1.4122, $\phi = 32\text{mm}$                                   | 1500     |
| 10   | Retaining Ring Internal, DIN 471-1.4122, $\phi = 22\text{mm}$                                   | 500      |
| 11   | Retaining Ring Internal, DIN 471-1.4122, $\phi = 28\text{mm}$                                   | 500      |
| 12   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 2 \times 5$                                    | 2000     |
| 13   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 2 \times 8$                                    | 2000     |
| 14   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 2 \times 10$                                   | 2000     |
| 15   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 2 \times 12$                                   | 2000     |
| 16   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 2.5 \times 10$                                 | 600      |
| 17   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 2.5 \times 12$                                 | 600      |
| 18   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 3 \times 5$                                    | 1500     |
| 19   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 3 \times 8$                                    | 3000     |
| 20   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 3 \times 10$                                   | 2500     |
| 21   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 3 \times 14$                                   | 1000     |
| 22   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 3 \times 16$                                   | 1500     |
| 23   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 3 \times 26$                                   | 1000     |
| 24   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 4 \times 8$                                    | 1000     |
| 25   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 4 \times 10$                                   | 1000     |
| 26   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 4 \times 20$                                   | 1000     |
| 27   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 5 \times 8$                                    | 1000     |
| 28   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 5 \times 10$                                   | 1000     |
| 29   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 5 \times 16$                                   | 2000     |
| 30   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 5 \times 20$                                   | 1000     |
| 31   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 6 \times 16$                                   | 1500     |
| 32   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 6 \times 20$                                   | 1500     |
| 33   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 6 \times 30$                                   | 1000     |
| 34   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 6 \times 35$                                   | 1500     |
| 35   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 8 \times 15$                                   | 1500     |
| 36   | Slotted Spring Dowel Pin, ISO 8752-1.4310, $\phi 8 \times 25$                                   | 1500     |
| 37   | Wedge Locking Washer M8 with Enlarged Outer Dia, NL8ss-254, Art. No 1572, Material: SS-245 SMO  | 160 Pair |
| 38   | Wedge Locking Washer M8, NL8ss-254, Art. No 1571, Material: SS-245 SMO                          | 80 Pair  |
| 39   | Wedge Locking Washer M10 with Enlarged Outer Dia, NL8ss-254, Art. No 1576, Material: SS-245 SMO | 100 Pair |
| 40   | Wedge Locking Washer M10, NL8ss-254, Art. No 1575, Material: SS-245 SMO                         | 80 Pair  |
| 41   | Wedge Locking Washer M12 with Enlarged Outer Dia, NL8ss-254, Art. No 1579 Material: SS-245 SMO  | 120 Pair |
| 42   | Wedge Locking Washer M12, NL8ss-254, Art. No 1578, Material: SS-245 SMO                         | 90 Pair  |