

Reduced shank bolts DIN 2510

SN	Description	Unit	Qty
1	BB0100D,Screw bolt Z 5/8" x 95 mm, DIN 2510, 1.7258 or 1.7218 (G) with two nuts Hex. NF 5/8",DIN 2510-m,1.1181(YK) +N	Each	60
2	BB0100D,Screw bolt Z 7/8" x140 mm, DIN 2510, 1.7258 or 1.7218 (G) with two Hex. Nut NF 7/8",DIN 2510-m,1.1181(YK) +N	Each	40
3	BB0100D,Screw bolt Z 1 1/8" x190 mm ,DIN 2510, 1.7258 or 1.7218 (G) with two Hex. Nut NF 1 1/8",DIN 2510-m,1.1181(YK) +N	Each	20
4	BB0100D,Screw bolt Z 1 1/4" x210 mm ,DIN 2510, 1.7258 or 1.7218 (G) with two Hex. Nut NF 1 1/4",DIN 2510-m,1.1181(YK) +N	Each	12
5	BB0100D,Screw bolt Z 1 1/2" x255mm ,DIN 2510, 1.7258 or 1.7218 (G) with two Hex. Nut NF 1 1/2",DIN 2510-m,1.1181(YK) +N	Each	20
6	BB0100D,Screw bolt Z 1 3/4" x320mm ,DIN 2510, 1.7258 or 1.7218 (G) with two Hex. Nut NF 1 3/4",DIN 2510-m,1.1181(YK) +N	Each	16
7	BB0100D,Screw bolt Z 2" x410mm ,DIN 2510, 1.7258 or 1.7218 (G) with two Hex. Nut NF 2",DIN 2510-m,1.1181(YK) +N	Each	16
8	BB0110D,Stud bolt HR 7/8" x120 mm ,DIN 2510, 1.7258 or 1.7218 (G) with one Hex. Nut 7/8",DIN 2510-m,1.1181(YK) +N	Each	10
9	BB0110D,Stud bolt HR 5/8"x80 mm,DIN 2510, 1.7258 or 1.7218 (G) with one Hex. Nut NF 5/8",DIN 2510-m,1.1181(YK) +N	Each	10