

## REQUIRED ANCHOR BOLTS FOR CEMENT MILL

MATERIAL OF ANCHOR BOLTS (ASTM F1554 GRADE 36 WITH MINIMUM YIELD TENSILE STRENGTH OF 380MPa)

### ANCHOR BOLT FOR MILL

NUMBER	TYPE	NOTES
8	ANCHOR BOLT M56x2220 DIN 7992	HAMMERHEAD T BOLT
8	HEX. NUT M56 DIN 934	
8	HEX. NUT M56 DIN 936	
8	WASER A57 DIN 125	

### ANCHOR BOLT FOR MAIN MOTOR

NUMBER	TYPE	NOTES
4	ANCHOR BOLT M36x1565 DIN 529/B	
4	HEX. NUT M36 DIN 934	
4	HEX. NUT M36 DIN 936	
4	WASER A37 DIN 125	

### ANCHOR BOLT FOR GEAR

NUMBER	TYPE	NOTES
4	ANCHOR BOLT M36x1565 DIN 529/B	
4	HEX. NUT M36 DIN 934	
4	HEX. NUT M36 DIN 936	
4	WASER A37 DIN 125	

### ANCHOR BOLT FOR GEAR RIM/PINION

NUMBER	TYPE	NOTES
8	ANCHOR BOLT M42x1725 DIN 7992	HAMMERHEAD T BOLT
8	HEX. NUT M42 DIN 934	
8	HEX. NUT M42 DIN 936	
8	WASER A43 DIN 125	

### ANCHOR BOLT FOR AUX. MOTOR AND GEAR

NUMBER	TYPE	NOTES
8	ANCHOR BOLT M30x970 DIN 529/B	
8	HEX. NUT M30 DIN 934	
8	HEX. NUT M30 DIN 936	

