



PT hexalobular socket,  
lens head screw ISO 7380  
with security pin



**Drawing to 3D CAD data**

accompanying data:  
D29903\_COVER\_SCREW\_50.pdf

Material : Steel case hardened 320-390HV  
zinc plated

Material color : -  
Surface : -

General tolerances: DIN ISO 2768-mK  
General radius : 0.1...0.3 mm  
General chamfer : 0.1...0.3 mm

50	23.03.2012	HTKB/LAM	series release
02	06.06.2011	HTKB/JKR	renamed
01	10.05.2011	HTKB/THO	First edition

VERSION	DATE	NAME	DESCRIPTION
---------	------	------	-------------

<b>CONFIDENTIAL</b>	Drawing type: <b>Part</b>			NAME	VISA	DATE
	FORMAT	SCALE	DRAWN by	<b>HTKB/THO</b>		<b>10.05.2011</b>
	<b>A4</b>	<b>4:1</b>	CHECKED by	<b>HTKB/LAM</b>		<b>23.03.2012</b>
			APPROVED by	<b>NNSA/FBN</b>		<b>23.03.2012</b>

PROJECT NAME	PROCESS	PROJECT N°:
<b>Pulse</b>	-	<b>613029100</b>
TITLE		FACTORY
<b>Cover_Screw</b>		<b>HQ Technical department</b>

SOURCE	DESTINATION	NUMBER	VERSION	SHEET
COUNTRY - COMPANY - FACILITY	COUNTRY - COMPANY - FACILITY		(DRAWING)	
<b>CH-30-3622</b>	-	<b>29903</b>	<b>50</b>	<b>1/1</b>