



| REF PART NO.                 | THREAD SIZE    | A     | B     | C     | D     | E     | F     | G     | H    | PANEL    |           |
|------------------------------|----------------|-------|-------|-------|-------|-------|-------|-------|------|----------|-----------|
|                              |                | ± 1.0 | ± 1.0 | ± 0.5 | ± 0.5 | ± 0.7 | ±0.03 | ± 0.5 | MAX  | Ø HOLE   | THICKNESS |
| ARDEN FASTENERS<br>12640 CIP | M6 X<br>1.0-6H | 23.5  | 13.5  | 14.5  | 12.5  | 6.3   | 0.89  | 6.6   | 13.1 | 10.3±0.3 | 3.4-6.3   |

3. COATING PER ASTM B117 OR EQUIVALENT FOR 72 MIN HRS
2. COLOR: ALUMINUM OR BLACK PERMISSIBLE
1. FREE FROM HYDROGEN EMBRITTLEMENT

This drawing is our property. It can't be reproduced or communicated without our written agreement.

**FIXOVED** FIXOVED FIXAÇÃO E VEDAÇÃO LTDA.

MATERIAL  
1050 SPRING STEEL

DESCRIÇÃO  
NUT CLIP

DRAWING BY \_\_\_\_\_ DATE \_\_\_\_\_

|            |                       |           |
|------------|-----------------------|-----------|
| SIZE<br>A4 | PART NUMBER<br>7150-9 | REV.<br>1 |
|------------|-----------------------|-----------|

|              |                      |              |
|--------------|----------------------|--------------|
| SCALE<br>2:1 | WEIGHT (KG)<br>0,005 | SHEET<br>1/1 |
|--------------|----------------------|--------------|