

Component name	Hexalobular socket countersunk flat head screw, ISO 14581			
ID number	9ADJ400400P0103			
BU Level ID	-			
Designation (suggestion)	SCR-CTSK-HL_ISO14581_M3X5-8.8/ZNBLC6F			
				Created: -
				Modified: -
				Status remarks:
Dimensions	symbol	value	unit	RoHS: compliant
nominal diameter of thread, d	d	M3	-	New constr: no restrictions
nominal length, l	l	5	Millimeters	New constr. comments:
height of the head, k	k	1.65	Millimeters	
hexalobular socket no.	-	T10	-	
diameter of the head, dk	dk	5.5	Millimeters	
thread, thd	thd	fully threaded	-	
thread length, b	b		Millimeters	
thread runout, a_max	a	1	Millimeters	
Properties				Other identity numbers
Mass (per 1000 items)	Mass	0,335	kg	S@NDY ID: 9ABA460288P0103
Material	Steel			
Property class	8.8 (ISO 898-1)			
Surface	Zinc electroplated, blue chromated, CrVI-free			
Surface thickness				
Surface details	ISO 4042			
Hardness range				
Reference standards	number	revision		
Corporate Standard				
Regional Standard (SaNDY)	HAQN401056	B 2014-01		
External Standard	ISO 14581	-		
Source supplier specification				
Remarks:				